

SPN 44: 1985

2.1.1 Tabel XIII A - Penghantar AAC

Penampang nominal (mm ²)	Jari-jari (mm)	Urut	GMR (mm)	Impedansi urutan positif (Ω /km)	Impedansi urutan nol (Ω /km)
16	2,2563	7	1,6380	1,8382+j 0,4033	1,9862+j 1,6910
25	2,8203	7	2,0475	1,1765+j 0,3895	1,3245+j 1,6770
35	3,3371	7	2,4227	0,8403+j 0,3791	0,9883+j 1,6666
50	3,9886	7	2,8957	0,5882+j 0,3677	0,7362+j 1,6552
70	4,7193	7	3,4262	0,4202+j 0,3572	0,5682+j 1,6447
95	5,4979	19	4,1674	0,3096+j 0,3460	0,4576+j 1,6339
120	6,1791	19	4,6837	0,2451+j 0,3375	0,3931+j 1,6250
150	6,9084	19	5,2365	0,1961+j 0,3305	0,3441+j 1,6180
185	7,6722	19	5,8155	0,1590+j 0,3239	0,3070+j 1,6114
240	8,7386	19	6,6238	0,1225+j 0,3157	0,2705+j 1,6032

2.1.2 Tabel XIII B - Penghantar AAAC

Penampang nominal (mm ²)	Jari-jari (mm)	Urut	GMR (mm)	Impedansi urutan positif (Ω /km)	Impedansi urutan nol (Ω /km)
16	2,2563	7	1,6380	2,0161+j 0,4036	2,1641+j 1,6911
25	2,8203	7	2,0475	1,2903+j 0,3895	1,4384+j 1,6770
35	3,3371	7	2,4227	0,9217+j 0,3790	1,0697+j 1,6665
50	3,9886	7	2,8957	0,6452+j 0,3678	0,7932+j 1,6553
70	4,7193	7	3,4262	0,4608+j 0,3572	0,6088+j 1,6447
95	5,4979	19	4,1674	0,3396+j 0,3449	0,4876+j 1,6329
120	6,1791	19	4,6837	0,2688+j 0,3376	0,4168+j 1,6251
150	6,9084	19	5,2365	0,2162+j 0,3305	0,3631+j 1,6180
185	7,6722	19	5,8155	0,1744+j 0,3239	0,3224+j 1,6110
240	8,7386	19	6,6238	0,1340+j 0,3158	0,2824+j 1,6033