

Starlite®

TRANSFORMATOR

JENIS : **TRAFO DISTRIBUSI (HERMETIK)** TYPE : **T 400 N 55**
 DAYA / KVA : **400 kVA** SERI NO : **1110291025 - 267**
 BEBAN : **KONTINIU** FASA : **3 Ø** FREKUENSI : **50 Hz**
 STANDAR : **SPLN D3.002-1:2007** KEL. VEKTOR : **Dyn 5**
 PENDINGINAN : **O N A N** PASANGAN : **LUAR / DALAM**
 T.I.D. : **LI 125 AC 50 / LI - AC 3** BAHAN BELITAN : **CU - AL**
 RUGI TANPA BEBAN : **595 W** RUGI BERBEBAN : **3850 W**
 KENAIKAN SUHU OLI MAKSIMUM : **50 °C** BERAT OLI : **620 KG.**
 KENAIKAN SUHU BELITAN MAKSIMUM : **55 °C** BERAT TOTAL : **2550 KG.**
 JENIS MINYAK : **MINERAL** TAHUN PEMBUATAN : **2011**

T.M.	SADAPAN	T.R.	T.M.	T.R.	IMPEDANSI
21 000	V 1				
20 500	V 2				
20 000	V 3				
19 500	V 4	400 V	11.54 A	577.3 A	4.0 %
19 000	V 5				
18 500	V 6				
18 000	V 7				



PT. ASATA UTAMA ELECTRICAL INDUSTRIES
 BUATAN INDONESIA
 MILIK P.L.N.

LMKO